

What is claimed is:

1. A water-swellaable waterproof sealant, which comprises water-absorbent resin particles (A) sealed within a polyhedron (B) composed of a water-permeable sheet.
2. The water-swellaable waterproof sealant of Claim 1, wherein said polyhedron (B) has a configuration such that said polyhedron (B) containing sealed therein swollen water-absorbent resin particles (A) after absorbing water has at least two planar faces.
3. The water-swellaable waterproof sealant of Claim 1, wherein said polyhedron (B) becomes rectangular or cubic after the water-absorbent resin particles (A) swollen absorbing water.
4. The water-swellaable waterproof sealant of Claim 1, wherein said polyhedron (B) is provided with a stitch on the side.
5. The water-swellaable waterproof sealant of Claim 1, wherein the inside of said polyhedron (B) is partitioned into a plurality of rooms, at least one of the rooms being a closed chamber and the rest of the rooms being an open chamber leading to the outside of the polyhedron (B), said water-absorbent resin particles (A) being sealed within said closed sealed chamber, said open chamber being provided with a feeding mouth in order to feed a heavy solid thereinto.
6. The water-swellaable waterproof sealant of Claim 1, wherein said water-absorbent resin particles (A) has an average particle diameter of $100 - 850 \mu\text{m}$, a rate of swelling of $3 - 50$ seconds, a water absorbency of $20 - 1,000 \text{ g/g}$, a ratio of a water retention to water absorbency of $0.55 - 1.00$, a gel modulus of $2 \times 10^3 - 12 \times 10^3 \text{ N/m}^2$, a water soluble content of not more than 30% by mass, a residual water soluble monomer content of not more than 500 ppm, and a blocking resistance to moisture of not more than 9%.
7. The water-swellaable waterproof sealant of Claim 1, wherein it takes $0.5 - 5$ minutes to increase the weight of said water-swellaable waterproof sealant by 15 kg when immersed in deionized water.
8. A waterproof sealant formed by water-absorption of the water-swellaable waterproof sealant of Claim 1.